

RAPPORTO DI PROVA NO. 2336.0UN0101/24

Test Report no.

METODO DI PROVA:

Test method

UNI 9175: 2010

DENOMINAZIONE DELLA PROVA:

Description of the standard

Reazione al fuoco mobili imbottiti.

Reaction to fire of upholstered products.

RICHIEDENTE:

Sponsor

CAMIRA FABRICS Ltd

Meltham Mills, Meltham, Huddersfield,
West Yorkshire, HD9 4AY (United Kingdom)

DENOMINAZIONE DEL MATERIALE:

Denomination of the material

Halcyon Aspen

PESO NOM. E LOTTO DEL MATERIALE: 420 g/m² - n. 552133

Nom. weight and batch of the material

DATA RICEVIMENTO CAMPIONI:

Date of the samples receipt

25/11/2024

Nota: Prova effettuata su ipotesi di mobile imbottito (Tessuto fornito dal Richiedente + Imbottitura fornita dal Laboratorio).

Note: Test effected on a upholstered piece of furniture hypothesis (Fabric supplied by the Sponsor + Filling supplied by the Laboratory).

- ☐ Il presente Rapporto di Prova è costituito da / This Test Report consists of:
- no. 4 pagine (compresa la presente) / no. 4 pages (including this one).
 - no. 2 allegati / no. 2 annexes.
- ☐ I risultati riportati in questo Rapporto di Prova si riferiscono esclusivamente al materiale sottoposto a prova fornito dal Richiedente (rif. codice Laboratorio no. 2336/24). Un campione del materiale è stato conservato dal Laboratorio.
- The results reported in this Test Report refer exclusively to the material submitted to test and supplied by the Sponsor (ref. Laboratory code no. 2336/24). A sample of the material has been retained by the Laboratory.*
- ☐ Questo Rapporto di Prova, valido esclusivamente per il materiale provato, non è rilasciato ai sensi degli art. 8 e 10 del D.M. 26.06.84 e D.M. 03.09.01
- This Test Report is valid solely for the material tested, it is not issued according to art. 8 and 10 of D.M. 26.06.84 and D.M. 03.09.01*
- Il D.M. 03.09.2001 pubblicato nella G.U.R.I. serie generale n.242 del 17 Ottobre 2001 modifica ed integra il precedente D.M. 26.06.84.
- The D.M. 03.09.2001 published in G.U.R.I. serie generale n.242 of 17 October 2001 amends the preceding D.M. 26.06.84.*

Prato, 03/01/2025

Il Direttore del Laboratorio
The Director of the Laboratory

Dr. Luca Ermini



DESCRIZIONE DEL MATERIALE

Description of the material

Aspetto: tessuto di colore viola (vedi foto). / *Appearance: purple fabric (see photo).*

Composizione (*): lato tessuto: 51% Poliestere, 37% Poliestere riciclato, 12% Poliestere riciclato da tessile a tessile, spalmatura sul retro TriOnyx.

Composition (): fabric side: 51% Polyester, 37% Re-cycled polyester, 12% Textile to textile recycled polyester, TriOnyx performance backcoat.*

Spessore nominale / *Nominal thickness* (*): 0.8 mm. - Peso nominale / *Nominal weight* (*): 420 g/m².

Trattamenti ignifuganti / *Flame retardant treatments* (*): TriOnyx backcoat - Colore / *Colour* (*): Berry.

Lato esposto (*): indicato dal Richiedente (lato tessuto, spalmatura sul retro).

Side exposed (*): indicated by the Sponsor (fabric face, backcoat on rear).

Impiego (*): rivestimento per imbottiti. / *End use* (*): upholstery.

DESCRIZIONE DELLA PROCEDURA DI CAMPIONAMENTO (*)

Description of the sampling procedure

Il campionamento del tessuto è stato effettuato a cura del Richiedente dal lotto di produzione n° 552133 c/o lo stabilimento di Camira Fabrics Ltd sito in Meltham Mills, Meltham Mill Road, Meltham, West Yorkshire, HD9 4FA (United Kingdom), in data 18 Novembre 2024 (Vedi dichiarazione allegata).

Il Laboratorio non è stato coinvolto in alcuna operazione di campionamento della produzione.

I risultati del presente rapporto di prova si riferiscono al campione così come ricevuto.

The sampling of the product has been effected by the Sponsor from the production batch n° 552133 c/o the factory of Camira Fabrics Ltd sited in Meltham Mills, Meltham Mill Road, Meltham, West Yorkshire, HD9 4FA (United Kingdom), on 18th November 2024 (See declaration annexed).

The Laboratory has not been involved in any sampling procedure of the material from the production.

The results of this test report refer to the sample as received.

(*) - Informazioni fornite dal Richiedente. Il Laboratorio declina ogni responsabilità.

Information supplied by the Sponsor. The Laboratory declines any responsibility.

PREPARAZIONE E CONDIZIONAMENTO

Preparation and Conditioning

Il materiale è stato sottoposto al metodo di preparazione UNI 9176: D

Il materiale è stato condizionato come prescritto dal metodo applicato.

The material has been submitted to the preparation method UNI 9176: D

The material has been conditioned before testing as prescribed by the method in object.

PROCEDIMENTO DI PROVA

Test Procedure

La prova è stata eseguita secondo il metodo **UNI 9175**.

L'imbottitura impiegata, fornita dal Laboratorio è costituita da una schiuma poliuretanica espansa FR, con densità 35 kg/m³ (PF 35 della ditta Giuseppe Olmo S.p.A.), di CLASSE 1 IM.

L'imbottitura è stata sottoposta a (80±5)°C e (80±5)% U.R. per 72 ore, dopo le quali è stata condizionata in atmosfera standard a (23±2)°C e (50±5)% U.R. per più di 48 ore prima della prova.

*The test has been carried out according to the method **UNI 9175**.*

The filling used has been supplied by the Laboratory and consists of an expanded polyurethane flame retardant flexible foam, with density 35 kg/m³ (PF 35 by Giuseppe Olmo S.p.A.), belonging to CLASS 1 IM.

The filling has been stored for 72 hours at (80±5)°C and (80±5)% R.H., after which period it has been conditioned in standard atmosphere at (23±2)°C and (50±5)% R.H. for more than 48 hours.

LUOGO E DATA PROVA: Prato, 17/12/2024

Place and test date

Operatore / Operator

Dr. Luca Ermini

Rapporto di Prova / Test Report
no. 2336.0UN0101/24 del / of 03/01/2025

Rapporto di Prova no. 2336.0UN0101/24 Test Report no.		METODO DI PROVA / TEST METHOD UNI 9175		
Materiale / Material: -----				
COMPONENTE <small>COMPONENT</small>	N. SERIE PROVETTE <small>SPECIMENS SERIES N.</small>	ESITO PROVE PER I VARI TEMPI DI INNESCO (IN SECONDI) <small>TEST RESULT FOR THE APPLIED IGNITION TIMES (SECONDS)</small>		
		20	80	140
imbottitura <i>filling</i>	1°	POSITIVO / POSITIVE <small>(0 s postcomb. / afterflame time)</small>		
	2°	POSITIVO / POSITIVE <small>(0 s postcomb. / afterflame time)</small>		
manufatto completo <i>complete item</i>	1°	POSITIVO / POSITIVE <small>(20 s postcomb. / afterflame time)</small>		
	2°	POSITIVO / POSITIVE <small>(30 s postcomb. / afterflame time)</small>		
	1°		POSITIVO / POSITIVE <small>(0 s postcomb. / afterflame time)</small>	
	2°		POSITIVO / POSITIVE <small>(0 s postcomb. / afterflame time)</small>	
	3°			
	1°			POSITIVO / POSITIVE <small>(0 s postcomb. / afterflame time)</small>
	2°			POSITIVO / POSITIVE <small>(0 s postcomb. / afterflame time)</small>
	3°			
Metodo di preparazione UNI 9176: D Method of preparation UNI 9176: D				CLASSE / CLASS 1 IM
Note / Notes: - Lato esposto : indicato dal Richiedente (lato tessuto). - Side exposed : indicated by the Sponsor (fabric face). - L'IMBOTTITURA IMPIEGATA DAL LABORATORIO, E' COSTITUITA DA UNA SCHIUMA POLIURETANICA ESPANSA FR, CON DENSITÀ 35 kg/m ³ , DI CLASSE 1IM. - THE FILLING USED HAS BEEN SUPPLIED BY THE LABORATORY; IT IS MADE OF AN EXPANDED POLYURETHANE FLAME RETARDANT FLEXIBLE FOAM, WITH DENSITY 35 kg/m ³ , BELONGING TO CLASS 1IM. QUESTO RAPPORTO DI PROVA RISPETTA METODI E PROCEDURE PREVISTI ALL'ART. 3 DEL D.M. 26.06.1984 COME MODIFICATO DAL D.M. 03.09.2001. THIS TEST REPORT IS IN COMPLIANCE WITH METHODS AND PROCEDURES PRESCRIBED BY ART. 3 OF D.M. 26.06.1984 AS MODIFIED BY D.M. 03.09.2001.				
<div style="display: flex; justify-content: space-between; align-items: center;"> <div style="display: flex; align-items: center;"> <div style="margin-left: 10px;"> <p>S.p.A. LABORATORIO PREVENZIONE INCENDI <small>Legalmente riconosciuto - Autorizzato dal Ministero dell'Interno</small></p> </div> </div> <div style="text-align: right;"> </div> </div>				

LUOGO E DATA PROVA: Prato, 17/12/2024
Place and test date

Operatore / Operator
 Dr. Luca Ermini

VALUTAZIONE DEI RISULTATI / JUDGEMENT

Sulla base dei risultati ottenuti e relativamente ai campioni forniti dal Richiedente, al materiale in esame è attribuibile la **CLASSE 1 IM** di reazione al fuoco.

*On the basis of the obtained results and referring to the samples supplied by the Sponsor, the material is assigned to **CLASS 1 IM** of reaction to fire.*

Foto / Photos

Campione / Specimen 1



Foto 1: prima della prova / Picture 1: before testing




Foto 2: dopo la prova / Picture 2: after testing

Campione / Specimen 2



Foto 3: prima della prova / Picture 3: before testing



Foto 4: dopo la prova / Picture 4: after testing

LUOGO E DATA PROVA: Prato, 17/12/2024
Place and test date

Operatore / Operator
Dr. Luca Ermini

Responsible Person to contact : Luke Russell luke.russell@camirafabrics.com

Page1/2

TEST REQUEST HEADING (full address):

Camira Fabrics Ltd, Meltham Mills, Meltham, Huddersfield, West Yorkshire, HD9 4AY

INVOICE HEADING (full address):

Camira Fabrics Ltd, Hopton Mills, Mirfield, West Yorkshire, WF14 8HF

COMMERCIAL NAME OF THE ARTICLE ¹⁾:

Halcyon Aspen

☐ Technical data of the specimen ²⁾: (see annexed sheet for stratified and composite materials)Composition (%): **Fabric Face:** 51% Polyester, 37% Recycled Polyester, 12% Textile to Textile Recycled Polyester**Backing:** TriOnyx performance backcoatAppearance: **Plain woven fabric with performance backcoat**Colour: **Berry**Batch Number : **552133**Thickness (mm): **0.8 mm (nominal)**Weight (g/m²): **420 g/m² (nominal)**Density (kg/m³):Possible fire retardant treatment: **None**

The specimen is



Isotropic



Anisotropic

The specimen usually composes a side in view (Yes/No): **Yes**The two sides are identical (Yes/No): **No**If the two sides are not identical, identify which of the two must be tested: **Fabric face; backcoat on rear**End use of the article: (CURTAIN, WALL, FLOOR, CEILINGS, etc.) **Upholstery - Soft seating & task seating**Laying of the article (if stuck specify the type of glue g/m²):REQUESTED TESTS ON THE SPECIMEN ^{3) 5)}

- UNI 9175 – Classe 1 IM

IN ACCORDANCE TO SPEC. N. ³⁾REQUEST FOR MEASUREMENT UNCERTAINTY (ANNEXED TO THE TEST REPORT ⁶⁾): YES ☐ NO ☐NOTES ON THE SPECIMEN (POSSIBLE DEROGATIONS ³⁾) :

TO BE FILLED ONLY IN CASE OF TRANSPORTATION FIELD TESTS :

SAFETY DATA SHEET

N°

TECHNICAL DATA SHEET

N°

BATCH

N°

Date

Date

..... 18 / 11 / 2024

Stamp and

signature of Responsible

Notes (to be read to fill this form):

- 1) The commercial name of the article represents the exact name that will be written on the Test Report . It has to be univocal and match exactly to possible names written on the specimen. LA.P.I. reserves itself the right to not accept specimen whose identification is unclear or ambiguous.
- 2) Technical data reported below will be written on the Test Report as indicated by the reference specification. The side to be tested has to be clearly identified, marking it in a suitable way if possible.
- 3) List the tests to perform and their reference methods. If the tests have the purpose to verify the matching of a specimen to a specification, it is useful to mention it in this field and to enclose a copy of the specification. If not specified, we assume the request refers to the latest valid edition of the specification. Indicate in this field possible derogations to the method or supplementary procedures to apply during the test. Every derogation and/or supplementary procedure will be referred and described on the Test Report. In methods expecting a preliminary treatment of the specimen, indicate only if you don't want those treatments to be performed on the sample.
- 4) In case UNI EN ISO 3386 "Resistance to compression of low density materials" has to be effected, the material has to be sent to the Laboratory not before 72 hours from its production.
- 5) The evaluation performed by the Laboratory does not involve the approval of the product neither by the Laboratory nor by the Accreditation Body. Moreover, the mark of the Accreditation Body or any reference to the accreditation of the Laboratory shall not be used by the Customer in any way, and in particular shall not be reported in the product documentation on the product itself. A copy of the Test Report can be attached.
- 6) The Responsibility of LAPI SpA is limited to the value of the activities regarding tests requested
- 7) In case LAPI can not finish the tests for technical reasons attributable to LAPI SpA , tests will not be charged and no recourse in terms of additional costs will be due in respect of LAPI SpA
- 8) LAPI SpA submitted to test a prototype and LAPI is not responsible, in the event of a negative result of the test, of the previous marketing in case of not-compliance.
- 9) The customer / Producer, (who presents and signs the request to perform the laboratory tests) if does not properly and clearly explicit in the data sheets any safety risks arising from simple handling ,conditioning as a result of thermal cycling or destructive tests laboratory on of their own material, is responsible for any damage to people, equipment and property.
- 10) In case of witness to test (when allowed) LAPI is exempted from any responsibility for accidents and damages to people and things could happen during testing due to the material under testing.

TECHNICAL SHEET (facsimile)



A) MANUFACTURER: **CAMIRA FABRICS LTD**

B) COMMERCIAL NAME: **Halcyon Aspen**

C) DESCRIPTION OF THE MATERIAL: **Plain woven fabric with performance backcoat**

- 1) nature of components: **Fabric Face:** 51% Polyester, 37% Recycled Polyester, 12% Textile to Textile Recycled Polyester
Backing: TriOnyx performance backcoat

warp +/- 5% N° THREADS/ cm /10cm

weft +/- 5% N° THREADS/ cm /10cm

2) format: **140 cm**

The material is (isotropic/anisotropic with two sides equal/different)

Processing:

3) weight: **420 g/m² (nominal)**

A) COMPLEX OF DIFFERENT COMPONENT: **Upholstery - soft seating & task seating**

B) LAYING:

C) APPLICATION: **Upholstery - soft seating & task seating, curtains and panels**

D) MAINTENANCE: **Vacuum regularly. Wipe with a damp cloth using soap and water or use proprietary upholstery shampoo. For deeper cleaning use bleach or alcohol. Full details can be found in our cleaning and disinfection guide.**

Date: **18/11/2024**

Firm (Legal Representative)

FAC-SIMIL MODEL
TO BE COMPILED ON COMPANY'S HEADED PAPER



The undersigned

Luke Russell

in his/her capacity of legal representative of the Company

Camira Fabrics Ltd

declares that the sampling named **Halcyon Aspen**

and sent to be tested

was taken from the production batch n°

552133

c/o the factory, **Meltham Mills, Meltham Mill Road, Meltham West Yorkshire**

on (day:) **18** (month:) **11** (year:).... **2024**

safety sheet n° (to be annexed with stamping).....

technical data sheet n° (to be annexed with stamping).....

Date,..... **18 / 11 / 2024**

Signature

NOTE: IF THE REQUIRED DATA WERE NOT AVAILABLE, SUPPLY AS MANY DETAILS AS POSSIBLE IN ORDER TO IDENTIFY THE MATERIAL THE SAMPLING WAS TAKEN FROM
