

---

## FLAMMABILITY TEST CERTIFICATE – 74286

**COMPANY DETAILS:** CAMIRA TRANSPORT FABRICS  
THE WATERMILL, WHEATLMELTHAM MILLS, MELTHAM  
HOLMFIRTH, HD9 4FA

**CONTACT NAME(S):** LUKE RUSSELL  
**TEL:** 01924 481 368  
**EMAIL:** [luke.russell@camirafabrics.com](mailto:luke.russell@camirafabrics.com)

**DATE RECEIVED:** 05/04/2019  
**DATE TESTED:** 12/04/2019  
**DATE ISSUED:** 12/04/2019  
**PO NUMBER:** 81A03466

---

**SAMPLE DESCRIPTION:** HYBRID BACKCOAT (130) (3 FRAME)  
**COLOUR:** RED  
**QUALITY/BATCH REF:** 411153  
**MODEL REF:** Q205  
**COMPOSITION:** NOT STATED  
**SAMPLE END USE:** TRANSPORT UPHOLSTERY  
**MANUFACTURER:** NOT STATED  
**SUPPLIER/BUYER:** NOT STATED

---

**TEST METHOD(S):**  
BS 5852:2006 Clause 11 – Method of test for the ignitibility of upholstered composites ignition source 7.

**PRE-TREATMENT:**  
Water Soak procedure in accordance with Annex E of BS 5852:2006

**CONDITIONING:**  
The sample was conditioned for 72 hrs in ambient conditions for at least 24 hrs in a specified atmosphere at  $23 \pm 2^{\circ}\text{C}$  and  $50 \pm 5\%$  r h.

---

Authorised By:



Zeb Alam  
Operations Director

Mark Jones  
Quality Manager

Karen Brooks  
Managing Director

## FLAMMABILITY TEST CERTIFICATE – 74286

### TEST RESULTS:

“The Following test results relate only to the ignitibility of the combination of the materials under the particular conditions of test; they are not intended as a means of assessing the full potential fire hazard of the materials in use.”

### TEST RESULTS continued:

TEST CRITERIA – BS 5852:2006 Source 7	INITIAL TEST	REPEAT TEST
Flaming Ceased:	12.01	12.42
<b>PROGRESSIVE SMOULDERING CRITERIA (4.1)</b>		
	CUSTOMERS OWN CMHR 50	CUSTOMERS OWN CMHR 50
<b>FILLING MATERIAL USED:</b>		
b) Detectable amounts of smoke, heat or glowing 60 mins after crib ignition?	N	N
c) Displays unsafe escalating combustion, requires to be forcibly extinguished?	N	N
d) Smouldering consumed the test specimen within the duration of the test?	N	N
e) Smoulder to the extremities i.e. upper or lower margins, either side or to its full thickness?	N	N
f) On final inspection, any evidence of charring more than 100 mm in any direction (apart from upwards) from the original nearest position?	N	N
<b>FLAMING CRITERIA (4.2)</b>		
b) Flaming continued for more than 13 minutes after the ignition of the crib?	N	N
c) Displays unsafe escalating combustion, requires to be forcibly extinguished?	N	N
d) Flaming and/or smouldering consumed the test specimen within the duration of the test?	N	N
e) Flame front reaches the lower margin, either side or passes through the full thickness?	N	N
<b>TEST RESULTS</b>	<b>PASS</b>	<b>PASS</b>

### CONCLUSION:

The sample supplied **meets** the test criteria of BS 5852:2006 Clause 11, ignition source 7.

END OF REPORT