


Classic

camira

Classic

www.camirafabrics.com




Leaf
VAC27



Electric Blue
VAC28




Bright Red
VAC04



Siren
VAC20



Bright Orange
VAC29




Soft Jade
VAC30




Magenta
VAC26



Ember
VAC31




Lichen
VAC32



Marine
VAC33



Grape
VAC25



Trafalgar
VAC35




Aubergine
VAC10



Imperial
VAC12



Lincoln Green
VAC37



Ink
VAC07



Sand Crepe
VAC46

Photographic fabric scans are not colour accurate. Always request actual fabric samples before ordering.



Mustard
VAC38



White
VAC01



Mineral
VAC44



Burnt Orange
VAC39




Chalk
VAC34



Ivory
VAC41



Biscuit
VAC43




Silver
VAC17




Sandlewood
VAC40



Taupe
VAC03



Prussian Blue
VAC16




Honey
VAC24




Mushroom
VAC19



Anthracite
VAC05



Cuba
VAC06



Dark Blue
VAC45



Black
VAC08



Transport seating



Reg. 118



IMO FTP Code (Part 8)



Year guarantee

Classic is a soft touch genuine leather with a lightly corrected grain and pigmented finish. The expansive colour palette has been carefully assembled to give a wide array of colour options designed to work cohesively with other Camira upholstery fabrics and ancillary trims.

Classic can be used for upholstery, side panels, headrests and even colour coordinated piping to complement your vehicle interior. It is produced from European hides, which average 5m² in size to give improved yields and better utilisation.

Technical information

UK

Composition
100% Leather

Width
Hide sizes are up to 5 m²

Weight
800 g/m² ±5%

Thickness
0.9 ± 1.0 mm

Flexes
EN ISO 5402 50,000 Flexing cycles / 5 year guarantee (full details available)

Flammability
ECE Reg No. 118 Annexes 7 & 8
FMVSS 302
BS 5852 Ignition Source 5
IMO FTP Code (Part 8)
Note: Flammability performance is dependent on components used. Our certificates show what substrates have been used in our tests. For composite tests customers must ensure their complete furniture meets the necessary standards.

Light Fastness
5 (ISO 105 - B02)

Fastness to Rubbing
Wet: 4, Dry: 4 (ISO 105 - X12)

Maintenance
Vacuum regularly. Wipe with a damp cloth using soap and water or use proprietary upholstery shampoo. Full details can be found in our cleaning and disinfection guide.

Batch to batch variations in shade may occur within commercial tolerances. We reserve the right to alter technical specifications without notice. The Unregistered Design Rights and the Copyright in all designs are the exclusive property of Camira Fabrics Limited.

D

Zusammensetzung
100% Leder

Breite
5 m² durchschnittlich pro Haut

Gewicht
800 g/m² ±5%

Dicke
0.9 ± 1.0 mm

Flexes
EN ISO 5402 50,000 Flexing cycles / 5 Jahre Garantie (Details auf Anfrage)

Feuersicherung
ECE Reg No. 118 Annexes 7 & 8
FMVSS 302
BS 5852 Ignition Source 5
IMO FTP Code (Part 8)
Bemerkung: Die Schwerentflammbarkeit hängt von den verwendeten Komponenten ab. Unsere Zertifikate zeigen auf, welche Substrate bei den Tests verwendet wurden. Bei Verbundtests muss sichergestellt sein, daß das komplette Möbel den entsprechenden Standards entspricht.

Lichtechtheit
5 (ISO 105 - B02)

Reibechtheit
Nass: 4, Trocken: 4 (ISO 105 - X12)

Reinigung
Regelmässig absaugen. Mit einem feuchten Tuch mit Wasser und Seife abwischen oder mit einem geeigneten Polstershampoo behandeln. Weitere Informationen finden Sie in unserem Leitfaden zur Reinigung und Desinfektion.

Handelsübliche Farbabweichungen können auftreten und berechtigen nicht zur Reklamation. Wir behalten uns die Änderung technischer Spezifikationen vor. Die registrierten und nicht registrierten Urheberrechte der Dessinierungen sind ausschliessliches Eigentum der Camira Fabrics Limited.

F

Composition
100% Cuir

Largeur
Taille moyenne des cuirs: 5 m²

Poids
800 g/m² ±5%

Epaisseur
0.9 ± 1.0 mm

Flexiones
EN ISO 5402 50,000 Flexing cycles / Garantie 5 ans (renseignements complémentaires disponibles)

Flammabilité
ECE Reg No. 118 Annexes 7 & 8
FMVSS 302
BS 5852 Ignition Source 5
IMO FTP Code (Part 8)
Notez: La performance de flammabilité dépend des composantes utilisées. Nos certificats indiquent les substrats utilisés dans nos tests. Pour les tests composites, les clients doivent s'assurer que leurs meubles complets satisfont aux normes nécessaires.

Solidité à la lumière
5 (ISO 105 - B02)

Solidité au Frottement
Mouillé: 4, Sec: 4 (ISO 105 - X12)

Nettoyage
Passez l'aspirateur régulièrement. Essayez avec un chiffon humide avec de l'eau et du savon ou utilisez un shampoing pour tissus d'ameublement exclusif. Vous trouverez tous les détails dans notre guide de nettoyage et de désinfection.

Une variation de couleurs peut provenir (commerciallement tolérable). Nous réservons le droit de changer les spécifications techniques sans préavis. Les Droits de Conception non-enregistrés et les droits d'auteur de tous les motifs sont la propriétés exclusives de Camira Fabrics Limited.