


Lyon Road Industrial Estate : Kearsley : Bolton Lancashire : BL4 8NB

Tel: +44 (0) 1204 792858

Email: enquiries@ltslab.co.uk





TEST CERTIFICATE

CLIENT:	Camira Fabrics Meltham Mills, Meltham	Certificate Number:	UK2301747-1
	Huddersfield HD9 4AY	Date Received:	12/10/2023
	-	Date Issued:	18/10/2023
		Issue Number:	1
		Changes made from previous	issue (if applicable)
Contact:	Luke Russell		
Tel:	03330324733		
Email:	luke.russell@camirafabrics.com		

SAMPLE IDENTIFICATION

The information is this section is provided by the client and Lancashire Testing Services Ltd assumes no reponsibility or liability for its accuracy. Sample Name / Reference **RePlay Zero** Additional Names: Batch Ref/Number: 531484 Order Number: 83A24249 Colour: Move21 Fabric Composition: Customer:

SPECIFICATION		
	- A1:2011 Low Hazard	
TEST METHOD		
Flammability:	BS EN 1021-1:2006: Ignition source smouldering cigarette	
	BS EN 1021-2:2006: Ignition source match flame equivalent	
Pre-treatment:	None Requested -	

Conclusion

HAZARD CATEGORY TESTED TO: LOW HAZARD

The sample tested complies with the flammability requirements of BS7176:2007 + A1:2011 for the hazard category stated above taking into account uncertainty of HAZARD CATEGORY FLAMMABILITY LOW HAZARD CRITERIA MET:

Uncertainty of Measurement: ±1 second - timing measurements, ±1mm - dimensional measurements Comments:



Lyon Road Industrial Estate : Kearsley : Bolton Lancashire : BL4 8NB Tel: +44 (0) 1204 792858 Email: enquiries@Itslab.co.uk

www.ltslab.co.uk



TEST CERTIFICATE

Test Results:-

BS EN 1021-1:2006: Smouldering Cigarette Source

Assessment of the ignitability of upholstered furniture

"The following test results relate only to the ignitability of the combination of materials under the particular conditions of test; they are not intended as a means of assessing the full potential fire hazard of the materials in use."

Sample Code	UK2301747 -	1				
Sample Name / Reference	RePlay Zero					
Client	Camira Fabrics					
Date of test	17/10/2023					
Pre-Treatment	None Requested					
Filling Type	Carpenter/RX36	6110 Combustion Modified Fe	oam Density 34-36kg/m ³ /10)5-115N		
Size of test rig	Small: Back - 48	50 x 300 ± 2mm + Seat - 450) x 150 ± 2mm			
Test Conditions	Period h	Temperature ºC	Relative humidity %	Air Flow m/s	Volume m ³	
Conditioning of test specimens	≥24	23±2	50±5	≤0.2	-	
Testing conditions	-	10-30	15-80	0.05	≥6	
Testing Source	Smouldering Cigarette Source					
Testing time limit	60 minutes after	r placement of smouldering o	cigarette.			
			Test 1	Tes	st 2	
Time for cigarette to smoulder to completion (min:sec)			20.11	19.39		
3.1a Escalating combustion behaviour observed so that it was unsafe to continue the test and active extinction was necessary			NO	NO		
3.1b Smouldering which largely consumed the test assembly within the test period			NO	NO		
3.1c Smouldering to the extremities of the specimen, viz upper or lower margins, either side or to its full thickness, within the duration of the test			NO	NO		
3.1d Smouldering after one hour from the beginning of the test			NO	NO		
3.1e On final examination, evidence of active smouldering			NO	NO		
3.2 Occurrence of flames initiated by a smouldering source			NO	NO		
Test Result:			PASS	PASS		

RESULT:	SMOULDERING CIGARETTE SOURCE	PASS	
		1	

Please note that copies of this original certificate are not valid



Lyon Road Industrial Estate : Kearsley : Bolton Lancashire : BL4 8NB Tel: +44 (0) 1204 792858 Email: enguiries@Itslab.co.uk

www.ltslab.co.uk



TEST CERTIFICATE

Test Results:-

BS EN 1021-2:2006: Butane Source 1

Assessment of the ignitability of upholstered furniture

"The following test results relate only to the ignitability of the combination of materials under the particular conditions of test; they are not intended as a means of assessing the full potential fire hazard of the materials in use."

RESULT: BUTANE IGNITION SOURCE 1 PASS					PASS		
Test Result:		PASS	PASS		PASS		
3.2d flaming continued for more than 120 seconds after removal of the burner tube		NO	NO		NO		
3.2c Flame Front reached the lower margins, either side or to its full thickness, within the duration of the test		NO	NO		NO		
3.2b Burning which larely consumed the test assembly within the test period		NO	NO		NO		
3.1e On final examination, evidence of active smouldering		NO	NO		N	NO	
3.1d Smouldering after one hour from the beginning of the test		NO	NO		NO		
3.1c Smouldering to the extremities of the specimen, upper or lower margins, either side or to its full thickness, within the duration of the test		NO	NO		NO		
3.1b Smouldering which largely consumed the test assembly within the test period		NO	N	0	NO		
3.1a/3.2a Escalating combustion behaviour observed so that it was unsafe to continue the test and active extinction was necessary		NO	N	0	NO		
Time for flames out (sec)		1	1		()	
	•	Test 1	Tes	st 2	Tes	st 3	
Testing time limit		er removal of burner tube	(120 seconds	5)			
Testing Source	Butane Flame	Ignition Source 1	10	00	0.00	-0	
Testing conditions	≥24	<u> </u>	50 1 15-		<u>≤0.2</u> 0.05	- ≥6	
Test Conditions Conditioning of test specimens	-	Temperature ⁰C 23±2	Relative h		Air Flow m/s ≤0.2	Volume m	
Size of test rig	Small: Back - 4	50 x 300 ± 2mm + Seat - 45	1			· · · · · · · · · · · · · · · · · · ·	
Filling Type	- Carpenter/RX36110 Combustion Modified Foam Density 34-36kg/m ³ /105-115N						
Pre-Treatment	None Requeste	None Requested					
Date of test	17/10/2023						
Client	Camira Fabrics						
Sample Name / Reference	RePlay Zero						

Issue Number: 1

Please note that copies of this original certificate are not valid



Lyon Road Industrial Estate : Kearsley : Bolton Lancashire : BL4 8NB Tel: +44 (0) 1204 792858 Email: enquiries@Itslab.co.uk www.ltslab.co.uk



9630

TEST CERTIFICATE

Certificate Number: UK

UK2301747-1

Date of Issue:

17/10/2023

			PColling
Craig Allardice	Tony Alcock	John Marsh	Peter Collings
Laboratory Technician	Laboratory Technician	Laboratory Supervisor	Operations Manager

Decision Rule:

Lancashire Testing Services have measurement uncertainties for all test standards (available on request) and have applied these measurements to the test result.

The specific level of risk is < 2.5% as stated in ILAC-G8:09/2019. Unless otherwise indicated L.T.S will apply this rule to all measurements reported.

If the measurement result plus/minus the expanded uncertainty with a 95 % coverage probability overlaps the limit, it is not possible to state compliance or non-compliance. The measurement result and the expanded uncertainty with a 95 % coverage probability will then be reported. The report will include the actual value with the uncertainty range.

Lancashire Testing Services Ltd have conducted thorough analysis of the uncertainty of all measurements carried out in the application of the standard or standards detailed in this report. Where possible any associated uncertainty of measurements have been accounted for in the working instructions, so that they have no impact on the reporting of the final result. In instances were uncertainty of measurements can only be taken into account after the test has been conducted, these uncertainty values have been stated on this report. The stated uncertainty of measurement has also been taken into account in the final reporting of the overall result.

Information provided about a customer, from a source other than the customer, shall only be shared with the customer. The provider of the information shall remain confidential to the laboratory unless agreed by the source of the information.

Issue Number: 1

Please note that copies of this original certificate are not valid